

MPS-10系列

可調綫性直流電源



應用領域

- 生產綫工作臺常規測試、維修
- 實驗室、研究所
- 電子維修
- DIY電子愛好者

產品特性

- 10mV/1mA的顯示分辨率
- 輸出開關控制
- 面板鎖功能
- 電流高低檔切換
- 彩屏顯示，多參數一目了然

型號	MPS-11	MPS-12	MPS-13	MPS-14	MPS-15	MPS-16	MPS-17	MPS-18	MPS-19	
額定輸出電壓	0~30V	0~30V	0~30V	0~30V	0~30V	0~60V	0~60V	0~80V	0~100V	
額定輸出電流	0~2A	0~4A	0~6A	0~8A	0~10A	0~2A	0~4A	0~2A	0~0.5A	
額定輸出功率	60W	120W	180W	240W	300W	120W	240W	160W	50W	
負載調節率	電壓	0.05%+5mV	0.05%+5mV	0.05%+5mV	0.05%+8mV	0.05%+8mV	0.05%+5mV	0.05%+5mV	0.05%+5mV	0.05%+5mV
	電流	0.1%+5mA	0.1%+5mA	0.1%+5mA	0.1%+8mA	0.1%+5mA	0.1%+5mA	0.1%+5mA	0.1%+5mA	0.1%+5mA
電源調節率	電壓	0.05%+8mV	0.05%+5mV	0.05%+8mV	0.05%+10mV	0.05%+5mV	0.05%+8mV	0.05%+5mV	0.05%+5mV	0.05%+5mV
	電流	0.1%+5mA	0.1%+5mA	0.1%+5mA	0.1%+8mA	0.1%+5mA	0.1%+5mA	0.1%+5mA	0.1%+5mA	0.1%+5mA
設定分辨率	電壓	10mV	10mV	10mV	10mV	10mV	10mV	10mV	10mV	10mV
	電流	1mA	1mA	1mA	1mA	1mA	1mA	1mA	1mA	1mA
回讀分辨率	電壓	10mV	10mV	10mV	10mV	10mV	10mV	10mV	10mV	10mV
	電流	1mA	1mA	1mA	1mA	1mA	1mA	1mA	1mA	1mA
設置精確度 (25°C ± 5°C)	電壓	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+3字節	≤0.1%+3字節	≤0.1%+3字節
	電流	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+6字節	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+3字節
回讀精確度 (25°C ± 5°C)	電壓	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+2字節	≤0.1%+3字節	≤0.1%+3字節	≤0.1%+3字節
	電流	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+6字節	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+3字節	≤0.2%+3字節
紋波及噪聲 (25°C ± 5°C)	電壓	3mVrms	3mVrms	5mVrms	5mVrms	5mVrms	5mVrms	5mVrms	5mVrms	10mVrms
	電流	3mA rms	3mA rms	3mA rms	6mA rms	3mA rms	3mA rms	3mA rms	3mA rms	3mA rms