

WPS-380S系列

可编程开关直流电源

标配 RS-232 RS-485 USB

选配 LAN



应用领域

- 生产线工作台常规测试、维修
- 实验室、研究所
- 电子维修
- 自动化设备集成测试

产品特性

- 电压1mV电流0.1mA的分辨率，高精度显示
- 九组电压电流存储调出功能，方便快捷
- 智能温控风扇，实用至极
- list输出功能
- 数字键盘和旋钮两种方式设定电压电流
- 输出开关控制，轻松掌控
- 旋钮采用编码开关，使用方便快捷，具有防误调功能
- 电压电流区间设置功能

型号	WPS380S-40-60	WPS380S-80-30	WPS380S-200-12.5	WPS380S-360-7.5	WPS380S-500-5	WPS380S-800-3	WPS380S-1000-2.5	
额定输出电压	0-40V	0-80V	0-200V	0-360V	0-500V	0-800V	0-1000V	
额定输出电流	0-60A	0-30A	0-12.5A	0-7.5A	0-5A	0-3A	0-2.5A	
额定输出功率	800W	800W	800W	800W	800W	800W	800W	
负载调节率	电压	≤0.02%+8mV	≤0.02%+8mV	≤0.02%+8mV	≤0.02%+5mV	≤0.02%+5mV	≤0.02%+5mV	≤0.02%+5mV
	电流	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA
电源调节率	电压	≤0.02%+8mV	≤0.02%+8mV	≤0.02%+8mV	≤0.02%+5mV	≤0.02%+5mV	≤0.02%+5mV	≤0.02%+5mV
	电流	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA	≤0.02%+5mA
设定分辨率	电压	1mV	1mV	1mV	1mV	1mV	1mV	1mV
	电流	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA
设置精确度 (25°C±5°C)	电压	≤0.1%+8mV	≤0.1%+8mV	≤0.1%+8mV	≤0.1%+10mV	≤0.1%+10mV	≤0.1%+10mV	≤0.1%+10mV
	电流	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA
回读分辨率	电压	1mV	1mV	1mV	1mV	1mV	1mV	1mV
	电流	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA
回读精确度 (25°C±5°C)	电压	≤0.1%+8mV	≤0.1%+8mV	≤0.1%+8mV	≤0.1%+10mV	≤0.1%+10mV	≤0.1%+10mV	≤0.1%+10mV
	电流	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA	≤0.2%+2mA
纹波及噪声 (25°C±5°C)	电压	<8mVrms	<8mVrms	<8mVrms	<10mVrms	<10mVrms	<10mVrms	<10mVrms
	电流	<5mA _{rms}	<5mA _{rms}	<5mA _{rms}	<3mA _{rms}	<3mA _{rms}	<3mA _{rms}	<3mA _{rms}
温度系数	操作环境	0 to 40°C ≤ 80 R.H.						
	储存环境	-15 to 70°C ≤ 80 R.H.						
尺寸(W*H*D)	mm	111*170*250						
重量	kg	5						