

# Programmable Electrical Safety Tester

MST-8101/8103

Standard RS232



- 4.3-inch TFT color screen display, clear at a glance
- 105 test files can be compiled, and 25 test steps can be set for each file
- Current resolution up to 0.1μA, accurate
- Automatic discharge function after the test is over
- Up to 10GΩ insulation resistance test range
- 100VA capacity

Model		MST-8101	MST-8103
Function Description		AC	AC/DC/IR
Withstand voltage test			
lose Out Electricity Pressure	AC	voltage range	0.050kV—5.000kV
		Voltage waveform	Sine wave
		Distortion	< 3%
		working frequency	50、60Hz optional
		Frequency accuracy	±1%
		Output Power	100VA ( 20mA)
	DC	Voltage regulation rate	± (1.0% +50V) (rated power)
		voltage range	-
		Signal source frequency	-
		Output Power	50VA ( 10mA)
Voltage resolution		1V	
Voltage test accuracy		±2%	
Voltage generation method		DDS signal source plus class AB power amplifier	
Electricity flow Measurement test Fan Surround	AC	Current range	0.001mA – 20.00 mA
		Short circuit current (momentary)	>40 mA
		Current resolution	0.001 mA
		Current accuracy	± (2% of reading + 2 words)
	DC	Actual current	OFF-0.001 mA-20 mA
		Current range	-
		Current accuracy	-
Discharge function		Automatic discharge after the test ( DCW )	
Insulation resistance test ( MST-8103 only )			
The output voltage		0.050V – 1.000kV	
Voltage resolution		1V	
Voltage test accuracy		±2%	
Maximum output current		10mA	
Maximum output power		10VA (1000V/10mA)	
Output instantaneous short-circuit current		>20mA	
Load Regulation		≤ 1 % (rated power)	
Ripple ( 1kV )		≤ 3% (1kV , no load )	
Discharge function		Automatic discharge after the test	
Resistance measurement range		0.1MΩ– 10GΩ	
Resistance measurement accuracy		Voltage < 500V: 0.2MΩ ~ 1GΩ accuracy: [ ± 10% reading + 5 words ] 1GΩ ~ 10GΩ accuracy: [ ± 20% reading + 5 words ] Voltage > 500V: 0.2MΩ ~ 1GΩ accuracy: ± [3% reading + 5 words] 1GΩ ~ 10GΩ accuracy: ± [7% reading + 5 words]	
Arc detection		MST-8101	MST-8103
Measuring range	AC、DC	AC:1mA – 20mA (9 gears, fine-tuning )	AC、DC:1mA – 20mA(9 gears, fine-tuning )
Comparators			
Discrimination method		Window comparator mode I at the ON: When I at <I <sub>x</sub> < I <sub>on</sub> , the PASS; when I <sub>x</sub> ≤ I <sub>on</sub> or under I <sub>x</sub> ≥ I <sub>on</sub> , FAIL (article items I at < I <sub>on</sub> ) I down OFF: when I <sub>x</sub> < I <sub>up</sub> , PASS; when I <sub>x</sub> ≥ I <sub>up</sub> , FAIL; the insulation resistance judgment method is the same as above	
Capping current I <sub>on</sub>	AC、DC	AC: 0.001mA – 20mA	
Current upper limit setting I <sub>under</sub>	AC、DC	AC: 0.001mA – 20mA	
Resistance upper limit setting		OFF - 0.2MΩ - 10GΩ	
Resistance lower limit setting		0.2MΩ– 10GΩ	
Parameter setting			
Voltage rise time		0.1s – 999.9s	
Voltage drop time		0 s – 999.9s , ( only after the withstand voltage PASS )	
Voltage waiting time		0.3s - 999.9s ( only DC withstand voltage, and meet the rise time + test time > waiting time)	
Test time setting		0.3s - 999.9s (when TIMER ON )	
Time accuracy		±( 0.2% setting value ± 0.1s )	
Protocol		SCPI , Modbus	
storage		105 test files can be programmed , and 25 test steps can be set for each file	
interface		HANDLER , SINGAL , RS232C , RS485 ( optional )	
Size (W*H*D)	mm	215*143*405 ( without terminal )	
weight	kg	12	